



NOTE: Shown with standard shafts. Contact factory for nonstandard configurations.

Model	A	B-BOLT PATTERN	C	D	E	F
101	1 1/2	4 X 00.44 ON 4.0 B.C.D.	5.5	0.50	2.0	0.745 / 0.740 W/KEYWAYS (1) WOODRUFF 605 & (1) 3/16X1.0
201	1 3/4	4 X 00.44 ON 4.0 B.C.D.	5.4	0.50	1.3	00.868 / 0.866 W/KEYWAYS (1) WOODRUFF 605 & (1) 5/16X1.0
301	3	4 X 00.44 ON 4.0 B.C.D.	6.0	0.50	2.4	01.250 / 1.245 W/KEYWAYS (1) WOODRUFF 1009 & (1) 5/16X1.12
		4 X 00.688 ON 5.5 B.C.D.	6.0	0.63	2.4	
401	3 1/2	4 X 00.44 ON 4.0 B.C.D.	6.0	0.50	2.4	01.250 / 1.245 W/KEYWAYS (1) WOODRUFF 1009 & (1) 5/16X1.12
		4 X 00.688 ON 5.5 B.C.D.	6.0	0.63	2.4	
501	5	4 X 00.44 ON 4.0 B.C.D.	7.6	0.50	2.8	01.249 / 1.245 W/KEYWAYS (1) WOODRUFF 1009 & (1) 5/16X2.12
		4 X 00.688 ON 5.5 B.C.D.	8.0	1.05	2.4	
		4 X 00.812 ON 6.5 B.C.D.	8.0	1.05	2.4	
601		Consult Factory				