



	SIZE	MODEL	OPER.	A	B	C	D	E	F	G	H	J	WEIGHT(lbs)	(3)	(4)	(5)
ANSI 300	2	D621	201	27	15	6	10	11	11.125	6.5	7	2	151	NONE	1/2 NPT	1/2 NPT
	3	D621	201	27	15	7	10	11	15	8.25	7	2	164	NONE	1/2 NPT	1/2 NPT
	4	D621	301	29	20	9	14	13	18	10	12	3	391	NONE	1/2 NPT	1/2 NPT
	6	D621	401	49	27	11	20	13	22	12.5	15	4	553	NONE	1/2 NPT	1/2 NPT
	8	D621	401	50	28	12	20	13	27	15	14	4	1003	NONE	1/2 NPT	1/2 NPT
	10	D621	401	60	35	15	20	14	32.5	17.5	13	5	1720	NONE	1/2 NPT	1/2 NPT
	12	D621	401	68	38	21	20	15	38	20.5	15	5	3000	NONE	1/2 NPT	1/2 NPT
ANSI 600	2	D641	201	27	15	7	10	11	13	6.5	7	2	165	NONE	1/2 NPT	1/2 NPT
	3	D641	201	27	15	7	10	11	17.5	8.25	7	2	183	NONE	1/2 NPT	1/2 NPT
	4	D641	301	46	26	9	20	13	17	11	10	3.5	500	7/8 9UNC	1/2 NPT	1/2 NPT
	6	D641	401	48	27	11	20	13	22	14	12	3.5	671	NONE	1/2 NPT	1/2 NPT
	8	D641	501	57	33	13	20	15	26	16.5	8	5	1520	1-1/8-7UNC	1/2 NPT	1/2 NPT
	10	D641	501	60	35	14	20	14	31	20	11	5	2200	NONE	1/2 NPT	1/2 NPT
	12	D641	501	83	44	23	32	17	33	22	15	9	4200	NONE	1/2 NPT	1/2 NPT

(1) H-Minimum clearance required to replace slips.
 (2) Approximate Weights (Lbs.)
 (3) Number and size tapped holes.
 (4) Tapped bleeder hole.
 (5) Bottom plate drain hole.

(6) Contact factory for size requirements not listed
 (7) Dimensions are not certified.
 Contact factory for certified drawings.
 (8) Consult factory for additional sizes

Dimensions "F", "G" & "J" are exact. All others are rounded off to the nearest half-inch.