



	SIZE	MODEL	OPER.	A	B	C	D	E	F	G	H	J	WEIGHT(lbs)	(3)	(4)	(5)
ANSI 150	2	D711	101	21	12	4 ½	8	10 ½	7	6	3	1 ½	64	NONE	3/8 NPT	1/2 NPT
	3	D711	101	21	12	4 ½	8	10 ½	8	7 ½	3	1 ½	76	NONE	3/8 NPT	1/2 NPT
	4	D711	201	27	15 ½	7	10	11	9	9	4 ½	1 ¾	140	NONE	1/2 NPT	1/2 NPT
	6	D711	301	36	20 ½	8 ½	14	12 ½	10 ½	11	8	3	264	(4) ¾" 10 UNC	1/2 NPT	1/2 NPT
	8	D711	301	39 ½	22	10 ½	14	12 ½	11 ½	13 ½	11	3	436	(4) ¾" 10 UNC	1/2 NPT	1/2 NPT
	10	D711	301	42	23	12	14	12 ½	13	16	14	3	532	(4) 7/8" 9 UNC	1/2 NPT	1/2 NPT
	12	D711	401	55 ½	31	14 ½	20	12 ½	14	19	16	3 ½	844	(4) 7/8" 9 UNC	1/2 NPT	1/2 NPT
	14	D711	401	57	32 ½	16	20	12 ½	15	21	19	3 ½	1074	(4) 1" 8 UNC	1/2 NPT	1/4 NPT
	16	D711	501	67	39	18	20	14 ½	16	23 ½	21	5	1488	(8) 1" 8 UNC	1/2 NPT	1 NPT
	18	D711	501	67	39	18	20	14	17	25	21	5	1600	(8) 1.125" 8UNC	1 NPT	1/2NPT
	20*	D711	501	64	37	17	20	14 ½	40	27 ½	17	5	3326	NONE	1 NPT	1/4 NPT
	20**	D711RVP	501	74	40	25	20	15	32	27.5	35	5	2700	NONE	1 NPT	1/4 NPT
	24*	D711	501	78 ½	44	24 ½	20	14 ½	48	32	20	5	6264	NONE	1 NPT	1 NPT
	24**	D711RVP	501	82	44	30	20	15	36	32	42	5	4300	NONE	1 NPT	1/2 NPT
30	D711	601	98	56	31	32	17	60	38.8	35	9	13300	NONE	1 NPT	1 NPT	

(1) H-Minimum clearance required to replace slips.  
 (2) Approximate Weights (Lbs.)  
 (3) Number and size tapped holes.  
 (4) Tapped bleeder hole.

(5) Bottom plate drain hole.  
 (6) Contact factory for size requirements not listed  
 (7) Dimensions are not certified. Contact factory for certified drawings.

(8) Consult factory for additional sizes

Dimensions "F", "G" & "J" are exact.  
 All others are rounded off to the nearest half-inch.