



| | SIZE | MODEL | OPER. | A | B | C | D | E | F | G | H | J | WEIGHT(lbs) | (3) | (4) | (5) |
|----------|------|-------|-------|------|------|------|----|------|--------|------|-----|------|-------------|-----------------|---------|---------|
| ANSI 300 | 2 | D721 | 101 | 21 | 12 | 4 ½ | 8 | 10 ½ | 8 ½ | 6 ½ | 3 | 1 ½ | 78 | NONE | 3/8 NPT | 3/8 NPT |
| | 3 | D721 | 101 | 21 | 12 | 4 ½ | 8 | 10 ½ | 11 1/8 | 8 ¼ | 3 | 1 ½ | 102 | NONE | 3/8 NPT | 3/8 NPT |
| | 4 | D721 | 201 | 27 | 15 ½ | 7 | 10 | 11 | 12 | 10 | 4 ½ | 1 ¾ | 162 | NONE | 1/2 NPT | 1/2 NPT |
| | 6 | D721 | 301 | 36 | 20 ½ | 8 ½ | 14 | 12 ½ | 15 7/8 | 12 ½ | 8 | 3 | 348 | NONE | 1/2 NPT | 1/2 NPT |
| | 8 | D721 | 401 | 49 ½ | 28 | 11 | 20 | 12 ½ | 16 ½ | 15 | 11 | 3 ½ | 666 | (4) 7/8"- 9 UNC | 1/2 NPT | 1/2 NPT |
| | 10 | D721 | 401 | 52 | 29 | 12 ½ | 20 | 12 ½ | 18 | 17 ½ | 13 | 3 ½ | 888 | (4) 1"- 8 UNC | 1/2 NPT | 1/2 NPT |
| | 12 | D721 | 401 | 63 ½ | 36 ½ | 16 ½ | 20 | 14 ½ | 19 ¾ | 20 ½ | 16 | 5 | 1414 | (8) 11/8" 8 UNC | 1/2 NPT | 1/2 NPT |
| | 14 | D721 | 401 | 58 ½ | 34 ½ | 14 ½ | 20 | 14 ½ | 30 | 23 | 15 | 5 | 1990 | NONE | 1/2 NPT | 1/2 NPT |
| | 16 | D721 | 501 | 69 | 38 | 21 | 20 | 15 | 33 | 25.5 | 15 | 5 | 3400 | NONE | 1/2 NPT | 1/2 NPT |
| 18 | D721 | 501 | 69 | 38 | 21 | 20 | 15 | 36 | 28 | 15 | 5 | 3500 | NONE | 1/2 NPT | 1/2 NPT | |
| ANSI 600 | 2 | D741 | 201 | 24 ½ | 15 ½ | 15 ½ | 20 | 10 ½ | 11 ½ | 6 ½ | 2 ½ | 1 ½ | 100 | NONE | 1/2 NPT | 1/4 NPT |
| | 3 | D741 | 201 | 26 | 16 | 16 | 20 | 10 ½ | 14 | 8 ¼ | 3 ½ | 1 ½ | 142 | NONE | 1/2 NPT | 1/4 NPT |
| | 4 | D741 | 301 | 29 ½ | 19 | 19 | 20 | 11 | 17 | 10 ¾ | 4 | 1 ¾ | 230 | NONE | 1/2 NPT | 1/4 NPT |
| | 6 | D741 | 401 | 45 | 26 | 9 | 20 | 12 ½ | 22 | 14 | 10 | 3 ½ | 696 | NONE | 1/2 NPT | 1/4 NPT |
| | 8 | D741 | 401 | 48 | 27 | 11 | 20 | 13 ½ | 26 | 16 ½ | 12 | 5 | 1102 | NONE | 1/2 NPT | 1/4 NPT |
| | 10 | D741 | 501 | 62 ½ | 36 ½ | 16 | 20 | 14 ½ | 31 | 20 | 8 | 5 | 1974 | NONE | 1/2 NPT | 1/2 NPT |
| | 12 | D741 | 501 | 62 ½ | 38 | 17 | 20 | 14 ½ | 33 | 22 | 10 | 5 | 2532 | NONE | 1/2 NPT | 1/2 NPT |
| | 14 | D741 | 501 | 60 | 35 | 14 | 20 | 14 | 35 | 23 ¾ | 11 | 5 | 2500 | NONE | 1/2 NPT | 1/2 NPT |
| | 16 | D741 | 601 | 83 | 44 | 23 | 32 | 17 | 39 | 27 | 15 | 9 | 4700 | NONE | 1/2 NPT | 1/2 NPT |
| 18 | D741 | 601 | 83 | 44 | 23 | 32 | 17 | 43 | 29 | 15 | 9 | 5000 | NONE | 1/2 NPT | 1/2 NPT | |

(1) H-Minimum clearance required to replace slips.
 (2) Approximate Weights (Lbs.)
 (3) Number and size tapped holes.
 (4) Tapped bleeder hole.
 (5) Bottom plate drain hole.

(6) Contact factory for size requirements not listed
 (7) Dimensions are not certified.
 Contact factory for certified drawings.
 (8) Consult factory for additional sizes

Dimensions "F", "G" & "J" are exact. All others are rounded off to the nearest half-inch.