



CLASS	SIZE	MODEL	OPER.	A	B	C	D	F	G	H	WEIGHT(lbs)	(3)	(4)	(5)
ANSI 150	2	D711	100	17	11	4 ½	10	7	6	3	48	NONE	3/8 NPT	1/4 NPT
	3	D711	100	17	11	4 ½	10	8	7 ½	3	62	NONE	3/8 NPT	1/4 NPT
	4	D711	200	27	16	7	20	9	9	4 ½	132	NONE	1/2 NPT	1/4 NPT
	6	D711	300	32 ½	20 ½	9	20	10 ½	11	8	214	(4) ¾" 10 UNC	1/2 NPT	1/4 NPT
ANSI 300	2	D721	100	17	11	4 ½	10	8 ½	6 ½	3	54	NONE	3/8 NPT	1/4 NPT
	3	D721	100	17	11	4 ½	10	11 ⅛	8 ¼	3	76	NONE	3/8 NPT	1/4 NPT
	4	D721	200	27	16	7	20	12	10	5	158	NONE	1/2 NPT	1/4 NPT
*ANSI 600	2	D741	200	24 ½	15 ½	15 ½	20	11 ½	6 ½	2 ½	100	NONE	1/2 NPT	1/4 NPT
	3	D741	200	26	16	16	20	14	8 ¼	3 ½	142	NONE	1/2 NPT	1/4 NPT
	4	D741	300	29 ½	19	19	20	17	10 ¾	4	230	NONE	1/2 NPT	1/4 NPT

(1) H-Minimum clearance required to replace slips.  
 (3) Number and size tapped holes. Each flange.  
 (4) Tapped bleeder hole.

(5) Bottom plate drain hole.  
 (6) \*Gear Operator recommended for Class 600.  
 Contact factory for torque & turn data

Dimensions "F" & "G" are nominal.  
 All others are rounded off to the nearest half-inch.